



Technical Specs:
Insulator: Black glass filled polyester PPS-GF30-FR
Flammability: UL 94V-O
Sleeve: Brass
Contact clip(4/6 finger): Beryllium copper(C17200)/Phosphor Bronze
Accepted pin: Ø0.40 to 0.56mm
Forces: (polished steel gauge Ø0.43mm)
--Insertion 2 N typ
--Withdrawal 1 N typ
Mechanical life: min500 cycles
Rated current: 3A
Contact resistance: max 10mΩ
Dielectric resistance: Min 1000V RMS
Max.Processing Temp:230°C for30-60 seconds
(260°C for 10 seconds)

Ordering Information

PM 254 - * - N - Z - * - ** - C

No.of Rows 1=Single Row 2=Dual Row	No.of Pins 2=40Pin	Type Z=01 N=02 Z=03 N=04	Length (mm)	Contact G0:Gold G1:1u" Gold G2:3u" Gold G3:5u" Gold G4:10u" Gold G5:15u" Gold G6:30u" Gold S0:Gold Flash/Tin S1:Tin	Plating Flash	Round Pin (mm)
--	-----------------------	--------------------------------------	----------------	--	------------------	-------------------



		GENERAL TOLERANCE		制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
		DIM	TOL	审核 CHECK	产品名称 TITLE	2.54 单排 排母 圆直针	版本 REV.	A
		X.X	±0.30	批准 APPROVAL	产品料号 PART NO.	PM254-1-N-Z-3.0-XX-C	单位 UNITS	mm
		X.XX	±0.20	比例 SCALE	材料		页次 SHEET	1/1
		X.XXX	±0.10	投影 Projection				
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°				